

Xtremo

X-7100, X-7200 & X-7400

Complete ATM Services introduces the X-7100, X-7200 and X-7400...

These compact ATMs allow you to offer your customers access to their cash in your convenient, friendly and safe location.

The Xtremo can be equipped the way you want it, with optional features that include:

- Large 8" color screen
- Stand-alone or through-the-wall installation

The Xtremo features a PC-based operating system that makes software changes or additions safe, easy and economical. Its front access and modular parts make maintenance fast and simple.

No ATM can match Xtremo's rugged durability in the most demanding locations. Xtremos are engineered to minimize the number of mechanical parts. Fewer parts mean fewer breakdowns.

The result is that an Xtremo ATM will continue to dispense cash, provide prepaid convenience services and offer the simplest maintenance in the business long after competing ATMs have been replaced.



Xtremo

X-7100, X-7200 & X-7400



The attractive design, large colour screen, user-friendly interface and dip card reader make these machines popular with users in a broad range of leisure, hospitality, retail and convenience locations.

Height: 165cm **Width:** 45cm **Depth:** 55cm

Its compact size ensures that this reliable and easy-to-use ATM will fit comfortably into your business premises.

Complete ATM Services' lifetime parts and labour warranty ensures that your ATM is always ready to dispense cash, and allows you to relax and enjoy the benefits of increased profits and higher customer traffic.

ATM Specifications

Module	X-7100	X-7200/X-7400
Display	8" TFT Colour display with built-in Vandal Cover Resolution: 640 x 480	8" TFT Colour display with built-in Vandal Cover Resolution: 640 x 480
Keyboard/ EPP compliant	16 Numerical Keys, EPP with Triple DES 8 Function Keys	16 Numerical Keys, EPP with Triple DES 8 Function Keys
Card Reader	Dip Type (EMV 4.0 ISO 3-Track Read)	Dip Type (EMV 4.0 ISO 3-Track Read)
Printer Method	Direct Thermal Line Printer	Direct Thermal Line Printer
Print Characters	English, Numeric, Line, Symbol, ASCII 96 Characters etc.	English, Numeric, Line, Symbol, ASCII 96 Characters etc.
Paper Setting	Semi-auto loading method	Semi-auto loading method
Paper Width	79mm	79mm
Print Speed	100mm/sec (600 dots line/sec)	100mm/sec (600 dots line/sec)
Receipt Capacity	Max 150 mm F diameter	Max 150 mm F diameter
Power Supply	DC24V	DC24V
Cutter Life	300,000 cuts	300,000 cuts
Cassette Capacity	1,000 new notes	2,000 new notes (X-7200) 4,000 new notes (X-7400)
Dispensing Speed	Max. 5 Notes/sec	Max. 5 Notes/sec
Interface	Serial (RS232C)	Serial (RS232C)
Access Direction	Front Access	Front Access
Reject Box	Up to 40 notes	Up to 100 notes
Number of Cassettes	Single (Total: 1,000 notes)	Single - X-7200 (2,000 notes) Two - X-7400 (4,000 notes)
CPU	Intel PXA 255	Intel PXA 255
Main Memory	64 Mb SDRAM	64 Mb SDRAM
Fresh Memory	32M	32M
O/S	Windows CE	Windows CE
Modem	RS232 Serial Modem (GPRS Cellpad)	RS232 Serial Modem (GPRS Cellpad)
Journal	Electronic journal	Electronic journal
Language	Up to 7 languages	Up to 7 languages
Security	UL 291 Business Hours Safe La Gard Electronic Combination Lock	UL 291 Business Hours Safe La Gard Electronic Combination Lock
Power	220 VAC, 7A, 50/60Hz with Noise Filter	220 VAC, 7A, 50/60Hz with Noise Filter
Dimension	450 (W) _ 550 (D) _ 1650(H) mm	450 (W) _ 550 (D) _ 1650(H) mm
Weight	90 Kg	120 Kg
Maintenance Access	Front Access Operating Manual & Quick Reference Guide Remote Management Software Illuminated Topper	Front Access Operating Manual & Quick Reference Guide Remote Management Software Illuminated Topper